

## **3.5inch Wireless Door Viewer With Video Door Phone 2 in 1 with Nightvision Function PY-V3501-A**

**Widely Used for Home, Apartment, Office etc .**

**Indoor monitor installed on various kinds of doors,hanged not only on the wall or wall cabinet, but also on the desk, end table or dining table**

**Outdoor Camera easily connected with the electric lock, enjoying the function of power saving and unlocking**

Feature:

- (1) With 2.4G all-digital frequency hopping and encryption technology, effective range 200 meter without block, with strong anti-interference ability;
- (2) Infrared night vision, which could monitor and shoot the images in dark;
- (3) 3.5 inch colorful LCD display images;
- (4) Full-touch elegant design for indoor unit
- (5) Hands-free calling and intercom functions are equipped and the electric lock can be remotely controlled;
- (6) Built-in 12 chord music ringtone, and the ringtone and volume can be selected;
- (7) The indoor unit can display date and time;
- (8) Automatically take photos with time, and store about 100 photos;
- (9) The brightness, sound volume of calling and ringtone of the indoor unit can be adjusted;
- (10) The indoor and outdoor both use the BL-5J lithium battery which is convenient to buy.
- (11) Indoor unit standby time about one to two months, and can also work with power plugged in.
- (12) Outdoor controller can unlock under the condition of both powered on and off.

### **Technical Specification:**

#### **Indoor Monitor**

Screen Size 3.5inch TFT 320×240

Power Input AC 100-240V 50 / 60Hz

Power Output DC 5V/500MA

Size 141×87×20 mm

Battery BL-5J Lithium Battery 1320mAh

Charging Time 3 Hours

Installation 1. On the Table, Tea Table etc

2. Hang On the Wall etc

Standby Time 20 Days for 3.5inch Indoor Unit

#### **Outdoor Camera**

Light Source 6/4 LED Light  
Camera CMOS 300,000 Pixel,  
View Angle 92 degree  
Power Supply 5V 500MA Power Adapter/ BL-5J Lithium Battery  
Size 160×100×30mm  
Installation On the Wall/ Installation of Door Hole  
Material of Door Phone ABS+ Acrylic Panel  
Standby Time 1~2 Month  
Operating Temperature Range -20°C — +55°C  
Operating Humidity Range Less than 85%